



Feature -

- Compact size 0.9 mm high
- Good double action
- Tactile feeling


Applications -

- Shutter of still cameras
- and video cameras

► SPECIFICATIONS

SWITCH SPECIFICATIONS	
POLE - POSITION	Momentary action , 1P2T
CONTACT RATING	12 V DC , 50 mA
CONTACT RESISTANCE	100 mΩ max . 5 V DC ; 1 A , by Method of Voltage DROP
INSULATION RESISTANCE	100 MΩ min . 100 V DC for 1 minute
DIELECTRIC STRENGTH	Breakdown is not Allowable ; 250 V AC for 1 Minute
OPERATING FORCE	1*st 80 ± 40gf 2*nd 250 ± 60gf
OPERATING LIFE	30,000 cycles
OPERATING TEMPERATURE RANGE	-20°C ~ 70°C
TOTAL TRAVEL	1*st 0.25 ± 0.1 mm 2*nd 0.4 ± 0.15 mm

► HOW TO ORDER



TC005 SERIES

DOUBLE ACTION SWITCH

▶ DIMENSION	
TC005-N12AAA	
TC005-N12ABA	
▶ CIRCUIT DIAGRAM	▶ P.C.B LAYOUT
▶ REFLOW SOLDERING	▶ MATERIAL
	<ul style="list-style-type: none"> ■ COVER - NS2(C7521R-H) ■ INSULATION SPACER - PTFE ■ BASE - LCP+GF ■ TERMINAL - BRASS SILVER PLATING
	▶ UNIT WEIGHT
	<ul style="list-style-type: none"> ■ TC005-N12AAA : 0.1 ± 0.05 g / pcs ■ TC005-N12ABA : 0.1 ± 0.05 g / pcs